

	<b>Mar-Mac Wire, Inc.</b> 229 Mar Mac Wire Rd. McBee, SC 29101 843-335-5000	<b>Title:</b> Contractor Brand Coil Wire – 16 and 16.5 gauge	
		<b>Doc No.</b> S7SP034	<b>Rev. No.</b> 002
		<b>Product Grouping:</b> Contractor Construction Products	
		<b>Date:</b> 2/5/16	<b>Page</b> 1 of 1
		<b>Responsible Person:</b>	Tracy Gooding



**Contractor Brand 16 and 16.5 gauge Coil Wire Certification**

**Standard Requirements:**

Mar-Mac Contractor Brand Coil Wire is produced to conform to the ASTM A853 specification. Contractor Brand Coil Wire is supplied as a value product and is sourced from the most economical domestic or import source. As such, the product cannot be certified to a specific heat number and does not comply with the Buy American or Buy America standards.

**Chemical Requirements:**

Mar-Mac Contractor Brand Coil Wire is produced using a C1006 or C1008 grade of steel as specified in ASTM A510 and ASTM A1040.

**Physical Requirements:**

Mar-Mac Wire Contractor Brand Coil Wire is annealed in a “dead soft” annealing cycle. The wire used will be annealed to a tensile range of 40,000psi to 60,000psi.  
Gauge: 16    Wire Diameter: .0605” to .0645”.  
Gauge: 16.5    Wire Diameter: .056” to .060”.

**Packaging Requirements:**

Mar-Mac 16 and 16.5 gauge Contractor Coil Wire is supplied in 3.5 pound coils. There are 20 coils packaged in a box for a total weight of 70 pounds per carton. Boxes are then package 48 per pallet.

Any additional questions in regard to Mar-Mac Contractor Brand Coil Wire products can be directed to:

Tracy Gooding  
Technical Services Manager  
Mar-Mac Wire Company  
(843) 335-5000