

	Mar-Mac Wire, Inc. 229 Mar Mac Wire Rd. McBee, SC 29101 843-335-5000		Title: Premium Galv. Coil Wire Certification	
			Doc No. S7SP046	Rev. No. 001`
			Product Grouping: Premium Galvanized Coil Wire	
			Date: 6/18/14	Page 1 of 1
			Responsible Person:	Tracy Gooding



Premium Galvanized Coil Wire Certification

Standard Requirements:

Mar-Mac Wire Premium Galvanized Coil Wire meets “Buy American” standards. Mar-Mac Wire Premium Coil Wire conforms to the ASTM A641 specification.

Chemical Requirements:

Mar-Mac Premium Galvanized Coil Wire is produced using a C1006 to C1008 grade of steel as specified in ASTM A510 and ASTM A1040.

Physical Requirements:

Mar-Mac Wire Premium Galvanized Coil Wire is produced from a galvanized product that is produced with a regular coating and a soft temper as specified in ASTM A641.

Tensile Maximum: 75,000psi

Gauge:	18	16
Dia. Min.	.0455”	.0605”
Dia. Max.	.0495”	.0645”

Packaging Requirements:

Mar-Mac Wire Premium Galvanized Coil Wire is supplied in 3.5 pound coils. There are 20 coils packaged in a box for a total weight of 70 pounds per carton. Boxes are packaged 48 per pallet.

Any additional questions in regard to Mar-Mac Wire Premium Galvanized Coil Wire products can be directed to:

Tracy Gooding
 Technical Services Manager
 Mar-Mac Wire Company
 (843) 335-5000