

	Mar-Mac Industries, Inc. 229 Mar Mac Wire Rd. McBee, SC 29101 843-335-5000	Title: Premium Galv. Coil Wire Certification	
		Doc No. 5541	Prev. No. S7SP046
		Product Grouping: Premium Galvanized Coil Wire	
		Origin Date: 6/18/14	Rev. Date: 4/14/2023
		Responsible Person:	Tracy Gooding

Premium Galvanized Coil Wire Certification

Standard Requirements:

Mar-Mac Industries, Inc. Premium Galvanized Coil Wire meets “Buy American” standards and conforms to the ASTM A641 specification.

Chemical Requirements:

Premium Galvanized Coil Wire is produced using a C1006 to C1008 grade of steel as specified in ASTM A510 and ASTM A1040.

Physical Requirements:

Premium Galvanized Coil Wire is produced from a galvanized product that is produced with a “regular” coating and a soft temper as specified in ASTM A641.

Tensile Maximum: 75,000psi

Gauge:	18	16
Dia. Min.	.0455”	.0605”
Dia. Max.	.0495”	.0645”

Packaging Requirements:

Premium Galvanized Coil Wire is supplied in 3.5 pound coils. There are 20 coils packaged in a box for a total weight of 70 pounds per carton. Boxes are packaged 48 per pallet.

Any additional questions in regard to Mar-Mac Industries, Inc. Premium Galvanized Coil Wire products can be directed to:

Tracy Gooding
 Director of Technical Operations
 Mar-Mac Industries Inc.
 (843) 335-5000